

GBM-3000 Specifications

The specifications apply when the GBM-3000 is powered on for at least 30 minutes under +18°C~+28°C.



Model \ Func.	AC Resistance	DC Voltage
GBM-3300	0~3.2kΩ	0~300V
GBM-3080	0~3.2kΩ	0~80V

DISPLAY																																																	
Screen	3.5"(320 x240) TFT LCD																																																
Resistance	5 digits																																																
Voltage	6 digits																																																
TEST SPEED																																																	
Slow	3 time/second																																																
Medium	14 time/second																																																
Fast	25 time/second																																																
Ex. Fast	65 time/second																																																
RESISTANCE MEASUREMENT																																																	
Test Frequency	1kHz (±0.5Hz) Fixed																																																
Input Impedance	3mΩ ~ 300mΩ : 99kΩ, 3Ω ~ 3kΩ : 2MΩ																																																
Range	<table border="1"> <thead> <tr> <th>Range No.</th> <th>Range</th> <th>Max. scale</th> <th>Resolution</th> <th>Test Current</th> <th>Open-circuit Voltage (Vpp max)</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>3mΩ</td> <td>3.1000mΩ</td> <td>0.1μΩ</td> <td>100mA</td> <td>8V</td> </tr> <tr> <td>1</td> <td>30mΩ</td> <td>31.000mΩ</td> <td>1μΩ</td> <td>100mA</td> <td>8V</td> </tr> <tr> <td>2</td> <td>300mΩ</td> <td>310.00mΩ</td> <td>10μΩ</td> <td>10mA</td> <td>7V</td> </tr> <tr> <td>3</td> <td>3Ω</td> <td>3.1000Ω</td> <td>100μΩ</td> <td>1mA</td> <td>3V</td> </tr> <tr> <td>4</td> <td>30Ω</td> <td>31.000Ω</td> <td>1mΩ</td> <td>100μA</td> <td>2V</td> </tr> <tr> <td>5</td> <td>300Ω</td> <td>310.00Ω</td> <td>10mΩ</td> <td>10μA</td> <td>1.5V</td> </tr> <tr> <td>6</td> <td>3kΩ</td> <td>3200.0Ω</td> <td>100mΩ</td> <td>10μA</td> <td>1.5V</td> </tr> </tbody> </table>	Range No.	Range	Max. scale	Resolution	Test Current	Open-circuit Voltage (Vpp max)	0	3mΩ	3.1000mΩ	0.1μΩ	100mA	8V	1	30mΩ	31.000mΩ	1μΩ	100mA	8V	2	300mΩ	310.00mΩ	10μΩ	10mA	7V	3	3Ω	3.1000Ω	100μΩ	1mA	3V	4	30Ω	31.000Ω	1mΩ	100μA	2V	5	300Ω	310.00Ω	10mΩ	10μA	1.5V	6	3kΩ	3200.0Ω	100mΩ	10μA	1.5V
Range No.	Range	Max. scale	Resolution	Test Current	Open-circuit Voltage (Vpp max)																																												
0	3mΩ	3.1000mΩ	0.1μΩ	100mA	8V																																												
1	30mΩ	31.000mΩ	1μΩ	100mA	8V																																												
2	300mΩ	310.00mΩ	10μΩ	10mA	7V																																												
3	3Ω	3.1000Ω	100μΩ	1mA	3V																																												
4	30Ω	31.000Ω	1mΩ	100μA	2V																																												
5	300Ω	310.00Ω	10mΩ	10μA	1.5V																																												
6	3kΩ	3200.0Ω	100mΩ	10μA	1.5V																																												
Accuracy	<table border="1"> <thead> <tr> <th>Range No.</th> <th>Speed</th> <th>Accuracy</th> <th>Temperature Coefficient</th> </tr> </thead> <tbody> <tr> <td rowspan="4">0</td> <td>Slow</td> <td>±0.5%rdg ± 10dgt</td> <td rowspan="4">(±0.05%rdg ± 1dgt)/°C</td> </tr> <tr> <td>Medium</td> <td>±0.5%rdg ± 15dgt</td> </tr> <tr> <td>Fast</td> <td>±0.5%rdg ± 20dgt</td> </tr> <tr> <td>Ex. Fast</td> <td>±0.5%rdg ± 40dgt</td> </tr> <tr> <td rowspan="4">1~6</td> <td>Slow</td> <td>±0.5%rdg ± 5dgt</td> <td rowspan="4">(±0.05%rdg ± 0.5dgt)/°C</td> </tr> <tr> <td>Medium</td> <td>±0.5%rdg ± 7dgt</td> </tr> <tr> <td>Fast</td> <td>±0.5%rdg ± 7dgt</td> </tr> <tr> <td>Ex. Fast</td> <td>±1.0%rdg ± 8dgt</td> </tr> </tbody> </table>	Range No.	Speed	Accuracy	Temperature Coefficient	0	Slow	±0.5%rdg ± 10dgt	(±0.05%rdg ± 1dgt)/°C	Medium	±0.5%rdg ± 15dgt	Fast	±0.5%rdg ± 20dgt	Ex. Fast	±0.5%rdg ± 40dgt	1~6	Slow	±0.5%rdg ± 5dgt	(±0.05%rdg ± 0.5dgt)/°C	Medium	±0.5%rdg ± 7dgt	Fast	±0.5%rdg ± 7dgt	Ex. Fast	±1.0%rdg ± 8dgt																								
Range No.	Speed	Accuracy	Temperature Coefficient																																														
0	Slow	±0.5%rdg ± 10dgt	(±0.05%rdg ± 1dgt)/°C																																														
	Medium	±0.5%rdg ± 15dgt																																															
	Fast	±0.5%rdg ± 20dgt																																															
	Ex. Fast	±0.5%rdg ± 40dgt																																															
1~6	Slow	±0.5%rdg ± 5dgt	(±0.05%rdg ± 0.5dgt)/°C																																														
	Medium	±0.5%rdg ± 7dgt																																															
	Fast	±0.5%rdg ± 7dgt																																															
	Ex. Fast	±1.0%rdg ± 8dgt																																															

VOLTAGE MEASUREMENT				
Range	Range No.	Range	Max. scale	Resolution
	0	8V	±8.08000	10µV
	1	80V	±80.8000	100µV
	2*	300V	±303.000	1mV
Accuracy	* : 300V only for GBM-3300			
	Range No.	Speed	Accuracy	Temperature Coefficient
	0~2	Slow	±0.01%rdg ± 3dgt	(±0.001%rdg ± 0.3dgt)/°C
		Medium	±0.01%rdg ± 5dgt	
		Fast	±0.05%rdg ± 5dgt	
Ex. Fast		±0.10%rdg ± 6dgt		
OTHER FUNCTIONS				
Range Selection	Auto range, Hold range, Nom range			
Comparator	ABS, PER or SEQ			
Contact detection	OPEN & WIRE			
Buzzer	OFF, Pass, Fail			
Trigger	INT, EXT			
INTERFACE				
USB Host / USB Device / RS-232C / Handler				
POWER SOURCE				
AC 100-240, 50-60Hz; Consumption: 10W				
DIMENSIONS & WEIGHT				
264(W) x 107(H) x 309(D) mm, Approx. 2.8kg				

Cosinus Messtechnik GmbH * Rotwandweg 4 * D-82024 Taufkirchen
Tel.: 089-665594-0 * Fax: 089-665594-30 * Web: www.cosinus.de * eMail: office@cosinus.de