

## AC Digital Clamp Meters

### Multi-functional Handy Clamp with Long Battery Life



### SK-7602 **TRUE RMS** / SK-7603

#### FEATURES

- 290-hours long time measurement (SK-7603, with alkaline cells)
- 13 measurement functions in one small package.
- Rubber-molded rotary switch and trigger.
- Easy-to-clamp compact & beaked clamp head even for narrow conductors.
- True RMS (SK-7660), MAX/MIN and Difference measurement.

#### SPECIFICATIONS

Display	: 4000 count LCD, Maximum reading 4050
Sampling Rate	: 3 times / sec
Range Selection	: Auto Ranging
Conductor Diameter	: $\phi$ 27mm Max.
Power Supply	: 1.5V R03 or AAA Batteries (x 2)
CE Mark	: CAT III 300V, CAT II 600V and EMC
Dimensions	: 171(H) x 58(W) x 27(D)mm
Weight	: 140g
Accessories	: 100-63 Test Leads (x 1 set) 1015 Carrying Case (x 1) 1.5V R03 Batteries (x 2)

	Range	Accuracy
$\tilde{A}$ / Hz	AC Current	40A $\pm 1.5\%rdg \pm 5dgt$ (50Hz/60Hz)
	Frequency	400A $\pm 3.0\%rdg \pm 5dgt$ (40Hz to 400Hz)
$\tilde{V}$ / $\tilde{V}$ / Hz / %	DC Voltage	5Hz to 1kHz $\pm 0.2\%rdg \pm 2dgt$
	400mV	$\pm 1.0\%rdg \pm 3dgt$
	4V	
	40V	$\pm 1.0\%rdg \pm 2dgt$
	400V	
	600V	
$\tilde{V}$ / $\tilde{V}$ / Hz / %	AC Voltage	4V $\pm 1.5\%rdg \pm 5dgt$ (40Hz to 400Hz)
	40V	
	400V	
	600V	
Resistance	Frequency	5Hz to 49.99kHz $\pm 0.2\%rdg \pm 2dgt$
	Duty Cycle	5% to 95% $\pm 2.0\%rdg \pm 3dgt$
	400Ω	$\pm 1.5\%rdg \pm 5dgt$
	4kΩ	$\pm 0.7\%rdg \pm 3dgt$
	40kΩ	
Other Measurements	400kΩ	$\pm 1.2\%rdg \pm 5dgt$
	4MΩ	$\pm 3.0\%rdg \pm 5dgt$
	40MΩ	
	Functions	Continuity Test, Diode Test, Capacitance


#### OPTIONAL ACCESSORIES

- 940 Alligator Clips
- 948 Alligator Clips
- 793 Coil-Type Contact Pin

#### Easy & Useful

##### Easy - to - Clamp

SK-7602 / 7603's compact and beaked clamp heads assure easy clamping even for narrow conductors.



$\phi$  27mm MAX

##### Avoid Your Fingers Slips

SK-7602 / 7603 are always fit on your hand. Double-Molding Rubbers on a Function Switch and a Trigger avoid your fingers slips during operation.



##### Test Lead Holder

Fixable Test Lead on the side of SK-7602 / 7603 by inserting its hook into the holder socket. Useful for Voltage, Resistance, Capacitance Measurements, Continuity and Diode Tests.



## AC Digital Clamp Meters

### Pocket-sized Clamp Meter



### SK-7601

#### FEATURES

- Simple operation.
- Strong and beaked Clamp Head against twists.
- AUTO POWER OFF : turns off automatically after 12 minutes.
- Full Auto Ranging up to 300A AC.
- DISPLAY HOLD Function.
- With Carrying Case.

#### SPECIFICATIONS

Display	: 4000 count LCD, Maximum reading 4000
Sampling Rate	: 2.5 times / sec
Range Selection	: Auto Ranging
Conductor Diameter	: $\phi$ 27mm Max.
Power Supply	: 3V CR2032 Battery (x 1)
CE Mark	: CAT III 300V and EMC
Dimensions	: 150(H) x 52(W) x 24(D)mm
Weight	: 110g
Accessories	: 1004 Carrying Case (x 1) 3V CR2032 Battery (x 1)

	Range	Accuracy
AC Current	40A	$\pm 1.8\%rdg \pm 5dgt$
	300A	
Functions	Display Hold, Auto Power OFF	