



MODEL 1110

DC V AC V DC A Ω ••• °C

- High sensitivity DC20kΩ/V
- 1m drop-proof heavy duty design
- Can measure line voltage up to AC 600V (Voltage to ground MAX AC 300V) (Protected by 600V ceramic fuse against accidental overload)
- Continuity buzzer, battery check, LED check function
- Skeleton type robust and clear case with carrying handle furnished as standard accessory

CE

	1110
DC V	0.3V(16.7kΩ/V) ±3% of FS 3/12/30/120/300/600V(20kΩ/V) ±3% of FS
AC V	12V(9kΩ/V) ±4% of FS 30/120/300/600V(9kΩ/V) ±3% of FS
DC A	60μA/30/300mA ±3% of FS
Ω	3/30/300kΩ ±3% of scale length
Continuity buzzer	Buzzer sounds below 100Ω
Battery Test	1.5V(0.7 - 2V) ±3% of FS (10Ω load)
Temperature	Possible with the temperature probe 7060 (discontinued).
LED	Approx. 10mA at 0Ω (at 3V of battery voltage)
Applicable Standards	IEC 61010-1 CAT III 300V / CAT II 600V, IEC 61326-1
Power source	R6(AA)(1.5V) × 2
Dimension	140(L) × 94(W) × 39(D)mm
Weight	Approx. 280g
Accessories	7066A(Test leads), 8923(Fuse[0.5A/600V]) × 1 (included), 1 (spare) R6(AA) × 2, 9103(Carrying case), Instruction manual

**COSINUS Messtechnik - Ihr Partner für Messlösungen
in allen elektrischen und physikalischen Anwendungen**

COSINUS Messtechnik GmbH

Rotwandweg 4

82024 Taufkirchen

Tel.: 089 / 66 55 94 - 0

Fax: 089 / 66 55 94 -30

**office@cosinus.de
www.cosinus.de**