

MODEL 5202

DIGITAL LIGHT METER



- 3 ranges changeable from low to high illuminance (200/2000/20000Lux)
- Data hold function
- Digital light meter with separate light receiving sensor and meter

CE

5202			
Ranges	0.1 - 19990Lux		
Accuracy (23°C±5°C)	Lux Accuracy		
	200 ±4%rdg±5dgt		
	2000 ±4%rdg±5dgt		
	20000 ±5%rdg±4dgt		
Current consumption	Approx. 2mA		
Response time	2.5 times / sec.		
Operating temperature and humidity range	0 - 50°C, relative humidity 80% or less (no condensation)		
Storage temperature and humidity range	-10 - 60°C, relative humidity 70% or less (no condensation)		
Angular incident light characteristics	30°less than ±3%	60°less than ±10%	80°less than ±30%
	Power source 6F22(9V) × 1		
	Dimension Meter:148(L) × 71(W) × 36(D)mm Light receiving sensor:80(L) × 67(W) × 32(D)mm		
Weight	Approx. 270g		
Accessories	Carrying case 6F22 × 1 Photocell cover Instruction manual		

**COSINUS Messtechnik - Ihr Partner für Messlösungen
in allen elektrischen und physikalischen Anwendungen**

COSINUS Messtechnik GmbH

Rotwandweg 4

82024 Taufkirchen

Tel.: 089 / 66 55 94 - 0

Fax: 089 / 66 55 94 -30

office@cosinus.de
www.cosinus.de